






WEBBING SLINGS 1-10 TONNE

Our durable Flat Web Slings are made with high-grade polyester and specially woven yarn, providing strength and durability. The eye on each end includes wear padding, giving you maximum protection during any tough job. Not only is this sling tough but it also complies with AS1353.1 and comes with an individual serial number and manufacturer's test certificate, so you can be sure that it meets the highest safety standards.



| Round Slings To AS4497:2018 | | | | Flat/Webbing Slings To AS1353.2-1997 | | | | |
|--------------------------------|------------|-------------|-------------|---|---|---|---|---|
| Flat Sling | Webb Width | Round Sling | Round Width |  |  |  |  |  |
| Code | mm | Code | mm | Kg | Kg | Kg | Kg | Kg |
| WBS01T | 50 | RDS01T | 47 | 1.000 | 800 | 2000 | 1.900 | 1.400 |
| WBS02T | 65 | RDS02T | 51 | 2.000 | 1.600 | 4.000 | 3.800 | 2.800 |
| WBS03T | 90 | RDS03T | 66 | 3.000 | 2.400 | 6.000 | 5.700 | 4.200 |
| WBS04T | 120 | RDS04T | 70 | 4.000 | 3.200 | 8.000 | 7.600 | 5.600 |
| WBS05T | 150 | RDS05T | 80 | 5.000 | 4.000 | 10.000 | 9.500 | 7.000 |
| WBS06T | 200 | RDS06T | 80 | 6.000 | 4.800 | 12.000 | 11.400 | 8.400 |
| WBS08T | 240 | RDS08T | 86 | 8.000 | 6.400 | 16.000 | 15.200 | 11.200 |
| WBS010T | 300 | RDS10T | 100 | 10.000 | 8.000 | 20.000 | 19.000 | 14.000 |