

POLYESTER HAUL ROPES

STAINLESS THIMBLES EACH END



FEATURES & BENEFITS

- Sewn eye each end fitted with Stainless Steel thimble
- Supplied on wooden reels
- Breakload tested and retains 100% published tensile
- In stock ex Sydney.
- Suitable for Arboriculture, working at heights, Telco and Industrial applications.
- Double braid construction in 100% high-tenacity Polyester High jacket to core ratio assisting long life
- Excellent breakload, UV and abrasion resistance
- Resistant to kinking, hocking and twisting
- Highly resistant to most chemicals
- Easy to splice

Product Code	Description	Stock Status	Break force Kg	UOM
ROPRBRY12150	12mm x 150m Haul Rope White/ Red fleck, sewn SS thimble eye each end	Stocked	3250	Reel
ROPRBRY12200	12mm x 200m Haul Rope White/ Red fleck, sewn SS thimble eye each end	Stocked	3250	Reel
ROPRBRY12250	12mm x 250m Haul Rope White/ Red fleck, sewn SS thimble eye each end	Stocked	3250	Reel
ROPRBRY16150	16mm x 150m Haul Rope White/ Blue fleck, sewn SS thimble eye each end	Stocked	5600	Reel
ROPRBRY16200	16mm x 200m Haul Rope White/ Blue fleck, sewn SS thimble eye each end	Stocked	5600	Reel
ROPRBRY16250	16mm x 250m Haul Rope White/ Blue fleck, sewn SS thimble eye each end	Stocked	5600	Reel

Rope Characteristics

Fibre type	Description	Specific gravity	Sensitive to	resistant to	heat reaction	Strength and elongation
Polyester	Continuous Filament	1.38	Alkalis, Phenolic Compounds, Sulfuric Acid.	Most Organic and Mineral Acids, Solvents, Bleaches and Oxidizing Agents.	Softens 228°C, Melts 255°C.	Equivalent wet/ dry strength ratio. Elongation 35% at Break.